

ORMANS TABLOSU E TABLE / جدول الأداء	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة													
					l/s	0	0.2	0.3	0.5	0.7	0.8	1.0	1.2	1.3	1.5	1.7	1.8	
					l/m	0	10	20	30	40	50	60	70	80	90	100	110	
					m³/h	0	0.6	1.2	1.8	2.4	3	3.6	4.2	4.8	5.4	6	6.6	
					Basma Yüksekliği / Head / ضغط الطرقي (m)	25	24	23	22	21	20	19	18	16	15	12	10	
PERFOR	4SPM5/4	4"	0.37	0.5	37	36	35	33	32	30	28	26	24	22	19	15		
	4SPM5/6	4"	0.55	0.75	49	48	46	44	42	40	38	35	32	29	25	20		
	4SPM5/8	4"	0.75	1	74	72	69	66	63	60	57	53	48	44	37	31		
	4SPM5/12	4"	1.1	1.5	92	89	86	83	79	75	71	66	61	55	47	38		
	4SPM5/15	4"	1.5	2	105	101	98	94	90	85	80	75	69	62	53	43		
	4SPM5/17	4"	1.5	2	117	113	109	105	100	95	90	84	77	69	59	48		
	4SPM5/19	4"	2.2	3	129	125	121	116	111	105	99	92	85	76	66	54		
	4SPM5/21	4"	2.2	3	142	137	132	127	121	115	109	101	93	84	72	59		
	4SPM5/23	4"	2.2	3	154	149	144	138	132	125	118	110	101	91	78	64		
	4SPM5/25	4"	2.2	3	166	161	155	149	142	135	128	119	109	98	84	69		
	4SPM5/27	4"	3	4	178	173	167	160	153	145	137	127	117	105	90	74		
	4SPM5/29	4"	3	4	191	185	179	171	164	155	146	136	125	113	97	79		
	4SPM5/31	4"	3	4	203	197	190	182	174	165	156	145	133	120	103	84		
	4SPM5/33	4"	3	4	215	209	202	193	185	175	165	154	141	127	109	89		
	4SPM5/35	4"-5"	3.7	5.5	234	227	219	210	200	190	180	167	153	138	119	97		
	4SPM5/38	4"-5"	3.7	5.5	246	239	230	221	211	200	189	176	161	146	125	102		
	4SPM5/40	4"-5"	3.7	5.5	259	251	242	232	222	210	198	185	169	153	131	107		
4SPM5/42	4"-5"	4	5.5	271	262	253	243	232	220	208	193	178	160	137	112			
4SPM5/44	4"-5"	4	5.5															

KNİK ÖLÇÜLER TECHNICAL DIMENSIONS / الأبعاد الفنية	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)					AĞIRLIK / WEIGHT / الوزن (kg)		
		kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكلبي
	4SPM5/4	0.37	0.5	230	M-360	590	96	98	9	2.5	11.5
	4SPM5/6	0.55	0.75	272	M-380	652	96	98	9.5	3.0	12.5
	4SPM5/8	0.75	1	314	M-400	714	96	98	10.5	3.6	14.1
	4SPM5/12	1.1	1.5	398	M-440	838	96	98	12.5	4.6	17.1
	4SPM5/15	1.5	2	461	M-470	931	96	98	14	5.5	19.5
	4SPM5/17	1.5	2	503	M-470	973	96	98	14	6.0	20.0
	4SPM5/19	2.2	3	545	M-560	1105	96	98	18.5	6.5	25.0
	4SPM5/21	2.2	3	587	M-560	1147	96	98	18.5	7.1	25.6
	4SPM5/23	2.2	3	629	M-560	1189	96	98	18.5	7.6	26.1
	4SPM5/25	2.2	3	671	M-560	1231	96	98	18.5	8.2	26.7
	4SPM5/27	3	4	713	T-529	1242	96	98	16.5	8.7	25.2
	4SPM5/29	3	4	755	T-529	1284	96	98	16.5	9.2	25.7
	4SPM5/31	3	4	797	T-529	1326	96	98	16.5	9.8	26.3
	4SPM5/33	3	4	839	T-529	1368	96	98	16.5	10.3	26.8
	4SPM5/35	3.7	5.5	881	T-599-695	1480-1576	96-126	98	20-38	10.9	30.9-48.9
	4SPM5/38	3.7	5.5	944	T-599-695	1543-1639	96-126	98	20-38	11.7	31.7-49.7
	4SPM5/40	3.7	5.5	986	T-599-695	1585-1681	96-126	98	20-38	12.2	32.2-50.2
	4SPM5/42	4	5.5	1028	T-599-695	1627-1723	96-126	98	20-38	12.7	32.7-50.7
	4SPM5/44	4	5.5	1070	T-599-695	1669-1765	96-126	98	20-38	13.3	33.3-51.3

İŞLETİM BİLGİLERİ OPERATING INFORMATION / معلومات التشغيل	Dönüş Yönü Rotation الدوران	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة
	Devir Speed السرعة	: 2900 RPM
	Çıkış Ağız Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded القياس الداخلي 1-1/2"
	Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)
	Frekans Frequency تردد التيار الكهربائي	: 50 Hz
	Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا (اختياري)	: 30 °C : 50 °C (Opsiyonel-Optional)
	Koruma Sınıfı Protection Degree درجة الحماية	: IP 68

MALZEME ÇİNSİ MATERIAL SPECIFICATIONS / مواد الخصائص	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستانلس ستيل



