

PERFORMANS TABLOSU جداول الأداء / PERFORMANCE TABLE	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة								
					l/s	0	19.4	22.2	25.0	27.8	30.6	33.3	36.1
					l/m	0	1164	1332	1500	1668	1836	1998	2166
		Inch	kW	HP	m³/h	0	70	80	90	100	110	120	130
	YSP SS 8110/1	4"-6"	7.5	10	Basma Yüksekliği / Head / ضغط العملي (m)	27	23	22	21	20	18	16	14
	YSP SS 8110/2	6"	15	20		55	45	44	42	39	36	33	28
	YSP SS 8110/3	6"-7"	22	30		82	68	65	63	59	55	49	43
	YSP SS 8110/4	6"-7"-8"	30	40		110	90	87	83	79	73	66	57
	YSP SS 8110/5	6"-7"-8"	37	50		137	113	109	104	99	91	82	71
	YSP SS 8110/6	7"-8"	45	60		165	135	131	125	118	109	99	85
	YSP SS 8110/7	7"-8"	52	70		192	158	152	146	138	127	115	99
	YSP SS 8110/8	7"-8"	60	80		220	180	174	167	158	146	132	114
	YSP SS 8110/9	7"-8"	67	90		247	203	196	188	177	164	148	128
	YSP SS 8110/10	8"-10"	75	100		275	225	218	209	197	182	165	142
	YSP SS 8110/11	8"-10"	81	110		302	248	239	229	217	200	181	156
	YSP SS 8110/12	8"-10"	92	125		329	270	261	250	236	218	197	170
	YSP SS 8110/13	8"-10"	92	125		357	293	283	271	256	237	214	185
	YSP SS 8110/14	10"	110	150		384	315	305	292	276	255	230	199
	YSP SS 8110/15	10"	110	150		412	338	326	313	296	273	247	213
	YSP SS 8110/16	10"	129	175		439	360	348	334	315	291	263	227
	YSP SS 8110/17	10"	129	175		467	383	370	354	335	309	280	241
	YSP SS 8110/18	10"	129	175		494	405	392	375	355	328	296	256
	YSP SS 8110/19	10"	147	200		522	428	413	396	374	346	313	270
	YSP SS 8110/20	10"	147	200		549	450	435	417	394	364	329	284
	YSP SS 8110/21	10"	166	225		576	473	457	438	414	382	345	298
	YSP SS 8110/22	10"	184	250		604	495	479	459	433	400	362	312

TEKNİK ÖLÇÜLER الأبعاد الفنية / TECHNICAL DIMENSIONS	POMPA TİPİ PUMP TYPE	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)				AĞIRLIK/ WEIGHT/ الوزن (kg)			
	نوع المضخة	kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكللي
	YSP SS 8110/1	7.5	10	686	795/678	1481/1364	95/142	213	28.8/43.5	32	60.8/75.5
	YSP SS 8110/2	15	20	842	911	1753	142	213	65	38	103
	YSP SS 8110/3	22	30	997	1006/840	2003/1837	142/172	213	76/81	45	121/126
	YSP SS 8110/4	30	40	1153	1217/940/996	2370/2093/2149	142/172/192	213	98/91/120	51	149/142/171
	YSP SS 8110/5	37	50	1309	1247/980/1056	2556/2289/2365	142/172/192	213	103/103/129	57	160/160/186
	YSP SS 8110/6	45	60	1465	1060/1116	2525/2581	172/192	213	113/138	64	177/202
	YSP SS 8110/7	52	70	1620	1218/1286	2838/2906	172/192	213	138/170	70	208/240
	YSP SS 8110/8	60	80	1776	1250/1286	3026/3062	172/192	213	149/170	76	225/246
YSP SS 8110/9	67	90	1932	1282/1341	3214/3273	172/192	213	160/185	83	243/268	
YSP SS 8110/10	75	100	2087	1366/1250	3453/3337	192/231	213	186/200	89	275/289	
YSP SS 8110/11	81	110	2243	1391/1310	3634/3553	192/231	213	195/228	95	290/323	
YSP SS 8110/12	92	125	2399	1471/1370	3870/3769	192/231	213	210/256	101	311/357	
YSP SS 8110/13	92	125	2554	1471/1370	4025/3924	192/231	213	210/256	108	318/364	
YSP SS 8110/14	110	150	2710	1430	4140	231	213	284	114	398	
YSP SS 8110/15	110	150	2866	1430	4296	231	213	284	120	404	
YSP SS 8110/16	129	175	3022	1510	4532	231	213	311	127	438	
YSP SS 8110/17	129	175	3177	1510	4687	231	213	311	133	444	
YSP SS 8110/18	129	175	3333	1510	4843	231	213	311	139	450	
YSP SS 8110/19	147	200	3489	1610	5099	231	213	338	145	483	
YSP SS 8110/20	147	200	3644	1610	5254	231	213	338	152	490	
YSP SS 8110/21	166	225	3799	1820	5619	231	213	400	159	559	
YSP SS 8110/22	184	250	3954	1820	4774	231	213	405	166	571	

İŞLETİM BİLGİLERİ معلومات التشغيل / OPERATING INFORMATION	Dönüş Yönü Rotation الدوران	
	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة	
Devir Speed السرعة	: 2900 RPM	
Çıkış Ağızı Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded القياس الداخلي 6 "	
Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)	
Frekans Frequency تردد التيار الكهربائي	: 50 Hz	
Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا	: 30 °C : 50 °C (Opsiyonel-Optional (اختياري)	
Koruma Sınıfı Protection Degree درجة الحماية	: IP 68	

MALZEME CİNSİ خصائص المواد / MATERIAL SPECIFICATIONS	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel (AISI 304L)
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel (AISI 304L)
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel (AISI 304L)
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel (AISI 304L)
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel (AISI 304L)
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel (AISI 420)



