

PERFORMANS TABLOSU جداول الأداء / PERFORMANCE TABLE	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة										
					l/s	0	0.3	0.7	1.0	1.3	1.7	2.0	2.3	2.7	3.0
					l/m	0	20	40	60	80	100	120	140	160	180
	Inch	kW	HP	m³/h	0	1.2	2.4	3.6	4.8	6	7.2	8.4	9.6	10.8	
	4SPM8/3	4"	0.55	0.75	Basma Yüksekliği / Head / الارتفاع الطولي (m)	18	17	16	16	15	14	13	12	10	8
4SPM8/5	4"	0.75	1	30		28	27	26	25	24	22	20	17	13	
4SPM8/7	4"	1.1	1.5	42		40	38	37	35	33	31	28	24	18	
4SPM8/10	4"	1.5	2	59		57	55	52	50	47	44	40	34	25	
4SPM8/12	4"	2.2	3	71		68	66	63	60	57	53	48	41	30	
4SPM8/15	4"	2.2	3	89		85	82	79	75	71	66	60	51	38	
4SPM8/17	4"	3	4	101		97	93	89	85	81	75	68	58	43	
4SPM8/20	4"	3	4	119		114	109	105	100	95	88	80	68	51	
4SPM8/23	4"-5"	3.7	5.5	137		131	126	121	115	109	101	92	78	58	
4SPM8/25	4"-5"	3.7	5.5	149		142	137	131	125	119	110	100	85	64	
4SPM8/27	4"-5"	4	5.5	160		153	147	141	135	128	119	107	92	69	
4SPM8/30	4"-5"	5.5	7.5	178		170	164	157	150	142	132	119	102	76	
4SPM8/33	4"-5"	5.5	7.5	196		187	180	173	165	156	145	131	112	84	
4SPM8/36	4"-5"	5.5	7.5	214		204	197	189	180	171	158	143	122	91	
4SPM8/38	4"-5"	7.5	10	226		216	207	199	190	180	167	151	129	97	
4SPM8/40	4"-5"	7.5	10	238		227	218	210	200	190	176	159	136	102	
4SPM8/43	4"-5"	7.5	10	255		244	235	225	215	204	189	171	146	109	
4SPM8/45	4"-5"	7.5	10	267	256	246	236	225	213	198	179	153	114		
4SPM8/47	4"-5"	7.5	10	279	267	257	246	235	223	207	187	160	119		

TEKNİK ÖLÇÜLER الابعاد الفنية / TECHNICAL DIM	POMPA TİPİ PUMP TYPE	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)					AĞIRLIK/ WEIGHT/ الوزن (kg)		
	نوع المضخة	kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكلي
	4SPM8/3	0.55	0.75	302	M-380	682	96	98	9.5	3.2	12.7
	4SPM8/5	0.75	1	386	M-400	786	96	98	10.5	4.2	14.7
	4SPM8/7	1.1	1.5	470	M-440	910	96	98	12.5	5.2	17.7
	4SPM8/10	1.5	2	596	M-470	1066	96	98	14	6.7	20.7
	4SPM8/12	2.2	3	680	M-560	1240	96	98	18.5	7.7	26.2
	4SPM8/15	2.2	3	806	M-560	1366	96	98	18.5	9.2	27.7
	4SPM8/17	3	4	890	T-529	1419	96	98	16.5	10.2	26.7
	4SPM8/20	3	4	1016	T-529	1545	96	98	16.5	11.7	28.2
4SPM8/23	3.7	5.5	1142	T-599-695	1741-1837	96-126	98	20-38	13.2	33.2-51.2	
4SPM8/25	3.7	5.5	1226	T-599-695	1825-1921	96-126	98	20-38	14.2	34.2-52.2	
4SPM8/27	4	5.5	1310	T-599-695	1909-2005	96-126	98	20-38	15.2	35.2-53.2	
4SPM8/30	5.5	7.5	1436	T-654-695	2090-2131	96-126	98	23-38	16.7	39.7-54.7	
4SPM8/33	5.5	7.5	1562	T-654-695	2216-2257	96-126	98	23-38	18.2	41.2-56.2	
4SPM8/36	5.5	7.5	1688	T-654-695	2342-2383	96-126	98	23-38	19.7	42.7-57.7	
4SPM8/38	7.5	10	1772	T-749-740	2521-2512	96-126	98	29.5-41	20.7	50.2-61.7	
4SPM8/40	7.5	10	1856	T-749-740	2605-2596	96-126	98	29.5-41	21.7	51.2-62.7	
4SPM8/43	7.5	10	1982	T-749-740	2731-2722	96-126	98	29.5-41	23.2	52.7-64.2	
4SPM8/45	7.5	10	2066	T-749-740	2815-2806	96-126	98	29.5-41	24.2	53.7-65.2	
4SPM8/47	7.5	10	2150	T-749-740	2899-2890	96-126	98	29.5-41	25.2	54.7-66.2	

İŞLETİM BİLGİLERİ معلومات التشغيل / OPERATING INFORMATION	Dönüş Yönü Rotation الدوران	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة
	Devir Speed السرعة	: 2900 RPM
	Çıkış Ağız Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded القياس الداخلي 2"
	Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)
	Frekans Frequency تردد التيار الكهربائي	: 50 Hz
	Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا	: 30 °C : 50 °C (Opsiyonel-Optional (اختياري)
	Koruma Sınıfı Protection Degree درجة الحماية	: IP 68

MALZEME CİNSİ خصائص المواد / MATERIAL SPECIFICATIONS	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel ستاتلس ستيل (AISI 304L)



