

TEKNİK ÖZELLİKLER/TECHNICAL SPECIFICATIONS


PERFORMANS TABLOSU / PERFORMANCE TABLE

POMPA TİPİ PUMP TYPE	MOTOR			KAPASİTE/CAPACITY											Basma Yüksekliği / Head (m)
				0	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	
				0	30	60	90	120	150	180	210	240	270	300	
	Inch	KW	HP	0	1.8	3.6	5.4	7.2	9	10.8	12.6	14.4	16.2	18	
4SVP14/3	4"	1.1	1.5	19	19	18	17	16	15	15	14	12	11	8	
4SVP14/4	4"	1.5	2	26	25	24	23	21	21	20	18	16	14	11	
4SVP14/5	4"	1.5	2	32	31	29	28	27	26	24	23	20	18	14	
4SVP14/6	4"	2.2	3	38	37	35	34	32	31	29	27	24	21	17	
4SVP14/7	4"	2.2	3	45	43	41	39	38	36	34	32	28	25	20	
4SVP14/8	4"	3	4	51	49	47	45	43	41	39	36	32	28	23	
4SVP14/10	4"	3	4	64	62	59	56	54	51	49	45	40	35	28	
4SVP14/11	4"	3	4	70	68	65	62	59	56	54	50	44	39	31	
4SVP14/12	4"-5"	3.7	5.5	77	74	71	68	64	62	59	55	49	43	34	
4SVP14/14	4"-5"	4	5.5	89	86	82	79	75	72	68	64	57	50	40	
4SVP14/15	4"-5"	4	5.5	96	93	88	84	81	77	73	68	61	53	42	
4SVP14/16	4"-5"	5.5	7.5	102	99	94	90	86	82	78	73	65	57	45	
4SVP14/18	4"-5"	5.5	7.5	115	111	106	101	97	92	88	82	73	64	51	
4SVP14/19	4"-5"	5.5	7.5	121	117	112	107	102	97	93	86	77	67	54	
4SVP14/20	4"-5"	7.5	10	128	123	118	113	107	103	98	91	81	71	57	
4SVP14/22	4"-5"	7.5	10	140	136	129	124	118	113	107	100	89	78	62	



TEKNİK ÖLÇÜLER / TECHNICAL DIMENSIONS

POMPA TİPİ PUMP TYPE	MOTOR		ÖLÇÜLER/DIMENSIONS (mm)					AĞIRLIK/WEIGHT (kg)		
	KW	HP	LP	LM	L	Ø M	Ø P	MOTOR	POMPA PUMP	TOPLAM TOTAL
4SVP14/3	1.1	1.5	326	M-440	766	96	98	12.5	3.5	16.0
4SVP14/4	1.5	2	376	M-470	846	96	98	14	4.1	18.1
4SVP14/5	1.5	2	426	M-470	896	96	98	14	4.7	18.7
4SVP14/6	2.2	3	476	M-560	1036	96	98	18.5	5.3	23.8
4SVP14/7	2.2	3	526	M-560	1086	96	98	18.5	5.9	24.4
4SVP14/8	3	4	576	T-529	1105	96	98	16.5	6.5	23.0
4SVP14/10	3	4	676	T-529	1205	96	98	16.5	7.7	24.2
4SVP14/11	3	4	726	T-529	1255	96	98	16.5	8.3	24.8
4SVP14/12	3.7	5.5	776	T-599-695	1375-1471	96-126	98	20-38	8.9	28.9-46.9
4SVP14/14	3.7	5.5	876	T-599-695	1475-1571	96-126	98	20-38	10.1	30.1-48.1
4SVP14/15	3.7	5.5	926	T-599-695	1525-1621	96-126	98	20-38	10.7	30.7-48.7
4SVP14/16	5.5	7.5	976	T-654-695	1630-1671	96-126	98	23-38	11.3	34.3-49.3
4SVP14/18	5.5	7.5	1076	T-654-695	1730-1771	96-126	98	23-38	12.5	35.5-50.5
4SVP14/19	5.5	7.5	1126	T-654-695	1780-1821	96-126	98	23-38	13.1	36.1-51.1
4SVP14/20	7.5	10	1176	T-749-740	1925-1916	96-126	98	29.5-41	13.7	43.2-54.7
4SVP14/22	7.5	10	1276	T-749-740	2025-2016	96-126	98	29.5-41	14.9	44.4-55.9



İŞLETİM BİLGİLERİ / OPERATION INFO.

Dönüş Yönü/Rotation :	Saatin Tersi/CCW
Devir/Speed :	2900-2950-3000 RPM
Çıkış Ağzı/Outlet Dia. :	İçten Pasolu / Inside Thread 2"
Frekans/Frequency :	50 Hz
Max. Su Sıcaklığı Max. Water Temp. :	95 °C
Koruma Sınıfı Protection Degree :	IP 68

MALZEME CİNSİ / MATERIAL SPECIFICATIONS

Ara Çanak/Stage :	(AISI 304L) (AISI 316L OPTIONAL)
Fan/Impeller :	(AISI 304L) (AISI 316L OPTIONAL)
Emiş Haznesi/Suction Case :	(AISI 304L) (AISI 316L OPTIONAL)
Çıkış Haznesi/Outlet Chamber :	(AISI 304L) (AISI 316L OPTIONAL)
Süzgeç/Stainer :	(AISI 304L) (AISI 316L OPTIONAL)
Pompa Mili :	(AISI 304L) (AISI 316L OPTIONAL)

