

PERFORMANS TABLOSU جدول الأداء / PERFORMANCE TABLE	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة								
					l/s	0	3	4	5	6	7	8	9
					l/m	0	180	240	300	360	420	480	540
		Inch	kW	HP	m³/h	0	10.8	14.4	18.0	21.6	25.2	28.8	32.4
	YSP SS 5300/1	4"	0.75	1	Basma Yüksekliği / Head / الضغط الطولي (m)	12	11	10	9	8	8	7	5
	YSP SS 5300/2	4"	1.5	2		23	21	20	18	17	15	13	10
	YSP SS 5300/3	4"	2.2	3		35	32	30	28	25	23	20	15
	YSP SS 5300/4	4"	3	4		47	42	39	37	34	31	26	20
	YSP SS 5300/5	4"-5"-6"	4	5.5		58	53	49	46	42	38	33	25
	YSP SS 5300/6	4"-5"-6"	4	5.5		70	63	59	55	51	46	39	30
	YSP SS 5300/7	4"-5"-6"	5.5	7.5		82	74	69	64	59	54	46	35
	YSP SS 5300/8	4"-5"-6"	5.5	7.5		93	84	79	73	68	62	52	40
	YSP SS 5300/9	4"-5"-6"	7.5	10		105	95	89	83	76	69	59	45
	YSP SS 5300/10	4"-5"-6"	7.5	10		117	105	99	92	85	77	65	50
	YSP SS 5300/11	6"	9.3	12.5		128	116	108	101	93	85	72	55
	YSP SS 5300/12	6"	9.3	12.5		140	126	118	110	102	92	78	60
	YSP SS 5300/13	6"	9.3	12.5		152	137	128	119	110	100	85	65
	YSP SS 5300/14	6"	11	15		163	147	138	128	119	108	91	70
	YSP SS 5300/15	6"	11	15		175	158	148	138	127	115	98	75
	YSP SS 5300/16	6"	13	17.5		187	168	158	147	136	123	104	80
	YSP SS 5300/17	6"	13	17.5		198	179	168	156	144	131	111	85
	YSP SS 5300/18	6"	15	20		210	189	177	165	152	138	118	90
	YSP SS 5300/19	6"	15	20		222	200	187	174	161	146	124	95

TEKNİK ÖLÇÜLER الأبعاد الفنية / TECHNICAL DIMENSIONS	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)					AĞIRLIK/ WEIGHT/ الوزن (kg)		
		kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكل
	YSP SS 5300/1	0.75	1	345	411	756	96	120	10.3	4.7	15
	YSP SS 5300/2	1.5	2	440	367	807	96	120	12.8	6.6	19.4
	YSP SS 5300/3	2.2	3	535	565	1100	96	120	17.4	8.5	25.9
	YSP SS 5300/4	3	4	630	522	1152	96	120	15	10.4	25.4
	YSP SS 5300/5	4	5.5	725	587/695/649	1312/1420/1374	96/132/142	120	18.3/38/40	12.3	30.6/50.3/52.3
	YSP SS 5300/6	4	5.5	820	587/695/649	1407/1515/1469	96/132/142	120	18.3/38/40	14.2	32.5/52.2/54.2
	YSP SS 5300/7	5.5	7.5	915	687/695/678	1602/1610/1593	96/132/142	120	22.5/38/43.5	16.1	38.6/54.1/59.6
	YSP SS 5300/8	5.5	7.5	1010	687/695/678	1697/1705/1688	96/132/142	120	22.5/38/43.5	18	40.5/56/61.5
YSP SS 5300/9	7.5	10	1105	768/740/758	1873/1845/1863	96/132/142	120	28.5/41/50	19.9	48.4/60.9/69.9	
YSP SS 5300/10	7.5	10	1200	768/740/758	1968/1940/1958	96/132/142	120	28.5/41/50	21.8	50.3/62.8/71.8	
YSP SS 5300/11	9.3	12.5	1295	800	2095	142	120	55	23.7	78.7	
YSP SS 5300/12	9.3	12.5	1390	800	2190	142	120	55	25.6	80.6	
YSP SS 5300/13	9.3	12.5	1485	800	2285	142	120	55	27.5	82.5	
YSP SS 5300/14	11	15	1580	851	2431	142	120	60	29.4	89.4	
YSP SS 5300/15	11	15	1675	851	2526	142	120	60	31.3	91.3	
YSP SS 5300/16	13	17.5	1770	911	2681	142	120	65	33.2	98.2	
YSP SS 5300/17	13	17.5	1865	911	2776	142	120	65	35.1	100.1	
YSP SS 5300/18	15	20	1960	973	2933	142	120	72	37	109	
YSP SS 5300/19	15	20	2055	973	3028	142	120	72	38.9	110.9	

İŞLETİM BİLGİLERİ معلومات التشغيل / OPERATING INFORMATION	Dönüş Yönü Rotation الدوران	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة
	Devir Speed السرعة	: 2900 RPM
	Çıkış Ağız Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded 2-1/2"
	Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)
	Frekans Frequency تردد التيار الكهربائي	: 50 Hz
	Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا	: 30 °C : 50 °C (Opsiyonel-Optional (اختياري)
	Koruma Sınıfı Protection Degree درجة الحماية	: IP 68

MALZEME CİNSİ خصائص المواد / MATERIAL SPECIFICATIONS	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel (AISI 420) ستاتلس ستيل



