

PERFORMANS TABLOSU جدول الأداء / PERFORMANCE TABLE	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة									
					l/s	0	6.9	13.9	19.4	22.2	25	27.8	30.6	33.3
					l/m	0	414	834	1164	1332	1500	1668	1836	1998
	Inch	kW	HP	m³/h	0	25	50	70	80	90	100	110	120	
YSP SS 6095/1	6"	3	4	Basma Yüksekliği / Head (m)	13	12	10	9	8	8	7	6	4	
YSP SS 6095/2	6"	7.5	10		26	24	20	18	17	16	14	11	7	
YSP SS 6095/3	6"	9.3	12.5		39	36	31	27	25	24	21	17	11	
YSP SS 6095/4	6"	13	17.5		53	48	41	36	34	32	28	23	14	
YSP SS 6095/5	6"	18.5	25		66	60	51	45	42	40	35	29	18	
YSP SS 6095/6	6"	18.5	25		79	72	61	54	50	47	42	34	21	
YSP SS 6100/7	6"	22	30		92	84	71	63	59	55	49	40	25	
YSP SS 6095/8	6"	26.5	35		105	95	82	72	67	63	57	46	28	
YSP SS 6095/9	6"	30	40		118	107	92	81	76	71	64	52	32	
YSP SS 6095/10	6"	37	50		131	119	102	90	84	79	71	57	35	
YSP SS 6095/11	6"	37	50		144	131	112	99	92	87	78	63	39	
YSP SS 6095/12	6"	37	50		158	143	122	108	101	95	85	69	42	
YSP SS 6095/13	7"	45	60		171	155	133	117	109	103	92	75	46	
YSP SS 6095/14	7"	45	60		184	167	143	126	118	111	99	80	49	
YSP SS 6095/15	7"	52	70		197	179	153	135	126	119	106	86	53	

TEKNİK ÖLÇÜLER الأبعاد الفنية / TECHNICAL DIMENSIONS	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)				AĞIRLIK/ WEIGHT/ الوزن (kg)			
		kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكل
	YSP SS 6095/1	3	4	568	649	1217	148	148	40	7	47
	YSP SS 6095/2	7.5	10	692	758	1450	148	148	50	10	60
	YSP SS 6095/3	9.3	12.5	817	800	1617	148	148	55	12	67
	YSP SS 6095/4	13	17.5	911	973	1884	148	148	65	15	80
	YSP SS 6095/5	18.5	25	1066	1006	2072	148	148	76	18	94
	YSP SS 6095/6	18.5	25	1190	1006	2196	148	148	76	20	96
	YSP SS 6100/7	22	30	1315	1106	2421	148	148	87	23	110
	YSP SS 6095/8	26.5	35	1439	1217	2656	148	148	98	26	124
YSP SS 6095/9	30	40	1564	1247	2811	148	148	103	28	131	
YSP SS 6095/10	37	50	1688	1347	3035	148	148	110	31	141	
YSP SS 6095/11	37	50	1813	1347	3160	148	148	110	34	144	
YSP SS 6095/12	37	50	1937	1347	3284	148	148	110	36	146	
YSP SS 6095/13	45	60	2062	1139	3201	148	148	127	39	166	
YSP SS 6095/14	45	60	2186	1139	3325	148	148	127	42	169	
YSP SS 6095/15	52	70	2311	1218	3529	148	148	138	44	182	

İŞLETİM BİLGİLERİ معلومات التشغيل / OPERATING INFORMATION	Dönüş Yönü Rotation الدوران	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة
	Devir Speed السرعة	: 2900 RPM
	Çıkış Ağız Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded 4"
	Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)
	Frekans Frequency تردد التيار الكهربائي	: 50 Hz
	Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا	: 30 °C : 50 °C (Opsiyonel-Optional (اختياري))
	Koruma Sınıfı Protection Degree درجة الحماية	: IP 68

MALZEME CİNSİ خصائص المواد / MATERIAL SPECIFICATIONS	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستاتلس ستيل
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel (AISI 420) ستاتلس ستيل



