

PERFORMANS TABLOSU جداول الأداء / PERFORMANCE TABLE	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك			KAPASİTE / CAPACITY / القدرة								
					l/s	0	22.2	27.8	33.3	38.9	44.4	50.0	55.6
					l/m	0	1332	1668	1998	2334	2664	3000	3336
	Inch	kW	HP	m³/h	0	80	100	120	140	160	180	200	
YSP SS 8160/1-C1	6"	9.3	12.5	Basma Yüksekliği Head / الارتفاع (m)	25	21	19	18	16	14	11	7	
YSP SS 8160/1	6"	11	15		30	25	24	22	21	19	16	13	
YSP SS 8160/2-B1-C1	6"	18.5	25		53	44	41	39	35	31	25	17	
YSP SS 8160/2	6"-7"	22	30		60	51	48	45	42	38	33	26	
YSP SS 8160/3-B3	6"-7"-8"	30	40		84	70	66	62	57	51	43	32	
YSP SS 8160/3	6"-7"-8"	37	50		90	76	72	67	62	57	49	40	
YSP SS 8160/4-B3-C1	6"-7"-8"	37	50		110	91	85	80	74	65	54	44	
YSP SS 8160/4	7"-8"	45	60		120	102	96	90	83	76	66	53	
YSP SS 8160/5-B3-C2	7"-8"	45	60		135	112	105	98	90	80	65	46	
YSP SS 8160/5	7"-8"	55	75		150	127	119	112	104	94	82	66	
YSP SS 8160/6-B5	8"	67	90		170	142	134	125	116	104	87	66	
YSP SS 8160/6	8"	75	100		180	152	143	134	125	113	99	79	
YSP SS 8160/7-B6	8"	75	100		199	166	155	146	135	121	102	77	
YSP SS 8160/7-B3	8"-10"	75	100		204	171	161	151	140	126	108	84	

TEKNİK ÖLÇÜLER الأبعاد الفنية / TECHNICAL DIMENSIONS	POMPA TİPİ PUMP TYPE نوع المضخة	MOTOR المحرك		ÖLÇÜLER / DIMENSIONS / الأبعاد (mm)					AĞIRLIK / WEIGHT / الوزن (kg)		
		kW	HP	LP	LM	L	ØM	ØP	MOTOR المحرك	POMPA PUMP المضخة	TOPLAM TOTAL الكل
	YSP SS 8160/1-C1	9.3	12.5	686	758	1444	142	213	50	34	84
	YSP SS 8160/1	11	15	686	800	1486	142	213	55	34	89
	YSP SS 8160/2-B1-C1	18.5	25	842	973	1815	142	213	72	40	112
	YSP SS 8160/2	22	30	842	1006/840	1848/1682	142/172	213	76/81	40	116/121
	YSP SS 8160/3-B3	30	40	997	1217/940/996	2214/1937/1993	142/172/192	213	98/91/120	47	145/138/167
	YSP SS 8160/3	37	50	997	1247/980/1056	2244/1977/2053	142/172/192	213	103/103/129	47	150/150/176
	YSP SS 8160/4-B3-C1	37	50	1153	1247/980/1056	2400/2133/2209	142/172/192	213	103/103/129	53	156/156/182
	YSP SS 8160/4	45	60	1153	1060/1116	2213/2269	172/192	213	113/138	53	166/191
	YSP SS 8160/5-B3-C2	45	60	1309	1060/1116	2369/2425	172/192	213	113/138	60	173/198
	YSP SS 8160/5	55	75	1309	1218/1286	2527/2595	172/192	213	138/170	60	198/230
	YSP SS 8160/6-B5	67	90	1465	1286	2751	192	213	170	66	236
	YSP SS 8160/6	75	100	1465	1341	2806	192	213	185	66	251
	YSP SS 8160/7-B6	75	100	1620	1341	2961	192	213	185	73	258
	YSP SS 8160/7-B3	75	100	1620	1366/1250	2986/2870	192/231	213	186/200	73	259/273

İŞLETİM BİLGİLERİ معلومات التشغيل / OPERATING INFORMATION	Dönüş Yönü Rotation الدوران	: Saatin Tersi Yönünde : CCW عكس عقارب الساعة
	Devir Speed السرعة	: 2900 RPM
	Çıkış Ağız Outlet Con. Dia. قطر مخرج التوصيل	: İçten Pasolu : Inside Threaded 6"
	Max. Gerilim Değişimi Voltage مقدار الفولط	: 380 - 415 V (+%6 - %10)
	Frekans Frequency تردد التيار الكهربائي	: 50 Hz
	Max. Su Sıcaklığı Max. Water Temp. درجة الحرارة العليا	: 30 °C : 50 °C (Opsiyonel-Optional (اختياري))
	Koruma Sınıfı Protection Degree درجة الحماية	: IP 68

MALZEME CİNSİ خصائص المواد / MATERIAL SPECIFICATIONS	Ara Çanak Stage مرحلة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستainless ستيل
	Fan Impeller مروحة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستainless ستيل
	Emiş Haznesi Suction Case قاعدة الشفط	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستainless ستيل
	Çıkış Haznesi Outlet Chamber المخرج	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستainless ستيل
	Süzgeç Strainer المصفاة	: Paslanmaz Çelik : Stainless Steel (AISI 304L) ستainless ستيل
	Pompa Mili Shaft عمود الارتكاز	: Paslanmaz Çelik : Stainless Steel (AISI 420) ستainless ستيل



